

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 December 2000 (21.12.2000)

PCT

(10) International Publication Number
WO 00/77468 A1

- (51) International Patent Classification⁷: **F28F 3/10**
- (21) International Application Number: **PCT/DK00/00319**
- (22) International Filing Date: **14 June 2000 (14.06.2000)**
- (25) Filing Language: **Danish**
- (26) Publication Language: **English**
- (30) Priority Data:
PA 1999 00838 14 June 1999 (14.06.1999) DK
- (71) Applicant (for all designated States except US): **APV HEAT EXCHANGER A/S [DK/DK]; Platinvej 8, DK-6000 Kolding (DK).**
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **PETERSEN, Jes, H. [DK/DK]; Hjarupvej 22, DK-6640 Lunderskov (DK). JENSEN, Benny [DK/DK]; Læssøegade 24, DK-6000 Kolding (DK).**
- (74) Agent: **HOFMAN-BANG A/S; Hans Bekkevolds Allé 7, DK-2900 Hellerup (DK).**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

[Continued on next page]

(54) Title: **A HEAT EXCHANGER PLATE AND SUCH A PLATE WITH A GASKET**



(57) Abstract: A heat exchanger plate (1) for a plate-type heat exchanger, said plate (1) comprising a gasket groove (6) in the form of an indentation that extends, at least across that portion of the plate, close to the periphery of the plate and is, at intervals, provided with an expanded portion (7) for receiving a coupling element (10) on an associated gasket (3). In connection with each of the expanded portions (7) of the gasket groove (6) there is, by cutting and ridging of plate material, provided at least two openings (8) substantially perpendicular to the longitudinal direction of the gasket groove, said openings (8) being configured for engaging with said coupling element (10). In the expanded portion (7) there is, substantially perpendicular to the gasket groove (6) provided at least one ridged, tongue-like portion (9), wherein said openings (8) are located at each side of the tongue-like portion (9) between this and the expanded portion (7) of the gasket groove (6).

WO 00/77468 A1